

commBOX

Interactive Classic



Available in 60", 75", 80" & 90"

The Classic Range of touchscreens remains Australia's favourite classroom touchscreen. Classic good looks, including a sturdy aluminium frame, toughened glass and rock-solid reliability makes the Classic Range a winner every time.



Greater Speed & Accuracy

Combining Infra-Red and camera technology, the Classic touchscreens are incredibly responsive and accurate. Incorporating multi-touch technology and gesture recognition there is no question why CommBox Touchscreens are replacing projectors and interactive whiteboards within classrooms and boardrooms both domestically and internationally.



Impressive from all Angles

All Classic touchscreens incorporate the highest Commercial Grade HD LED displays, rewarding the audience with superior image quality, excellent viewing angle and brightness. Paired with toughened Anti-Glare glass, which provides unmatched visibility from all angles of any light-filled room.



Plug & Play

Connect a Windows PC, Mac or laptop and interact immediately – No Drivers, no calibration required. CommBox Interactive touchscreens are truly plug & play. A Classic touchscreen comes ready to use straight out of the box, reducing installation time and costs.



A Smarter Investment

By utilising only the highest quality components a CommBox Touchscreen has a 17 year lifespan and does not require maintenance or replacement lamps.



Everyone Loves a Classic

The current Classic range has been further developed and now features stylish rounded corners, improved sound quality, increased inputs and an even sharper image.



The
Original
CommBox
Touchscreen...

Classic Specifications

Models



Classic 60



Classic 75



Classic 80



Classic 90

LED Display
Manufacturer

SAMSUNG
Commercial Grade

SAMSUNG
Commercial Grade

SAMSUNG
Commercial Grade

LG
Commercial Grade

Screen

Resolution

1920 x 1080p

1920 x 1080p

1920 x 1080p

1920 x 1080p

Brightness

450cd / m2

400cd / m2

400cd / m2

350cd / m2

Viewing Angle

178°

178°

178°

178°

Noise

Below 40dB 25C

Below 40dB 25C

Below 40dB 25C

Below 40dB 25C

Surface Temp

Below 10 at 24C

Below 10 at 24C

Below 10 at 24C

Below 10 at 24C

Operating Con

5C to 35C

5C to 35C

5C to 35C

5C to 35C

Touch

Points


4 (10 optional) Fingertips or anytips

Technology


Infra-Red & Optical




Dimensions




60"



75"



80"



90"

Display Area

Screen

1413(W) x 838(H) x
95(D)mm

1748(W) x 1024(H) x
110(D)mm

1840(W) x 1085(H) x
127(D)mm

2065(W) x 1222(H) x
125(D)mm

Packed

1590(W) x 960(H) x
270(D)mm

1930(W) x 1180(H) x
320(D)mm

2020(W) x 1230(H) x
315(D)mm

2250(W) x 1350(H) x
320(D)mm

Weight

Screen

50kg

80kg

100kg

114kg

Packed

57kg

92kg

112kg

134kg

Power

AC 100 to 240V, 50/60Hz Power Supply



Accessories

HDMI Cable
USB Cable

USB Extension Cable
Stylus Pen

Cleaning Cloth

Speakers

10W x 2 Internal Speakers
15W x 2 Speaker Out



Input/Output

HDMI x 3, VGA, Component,
AV, RS-232 Control, USB

