

# SB3260HDi



## 31.5" Signature Series True Outdoor All-Weather LCD Television for permanent outdoor installation

- Bright 31.5" LCD screen for improved outdoor viewing
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- ASA outdoor rated high-impact resin exterior
- Weatherproof built in 20W speakers
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-Out prevents unauthorized users from changing the programming.



### SCREEN

LCD Screen	31.5-inch diagonal TFT Active Matrix LCD
Resolution	1366 x 768 HD
Aspect Ratio	16:9
Contrast Ratio	3000:1
Frame Rate	60 Hz
Viewing Angle	178° x 178°
Response Time	6.5 milliseconds
TV formats	1080i, 720p, 576p, 576i

### PHYSICAL SPECS

Accessories Included	Weatherproof remote control and outdoor dust cover
Exterior	Resin
Exterior colour	Silver
TV Dimensions (cm)	81.8 W x 59 H x 17.7 D
TV Weight	16 kg
Shipping Dimensions (cm)	94 W x 81.2 H x 30.5 D
Shipping Weight	25 kg
Warranty	One-year parts and labour

### CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 2
Video Composite	S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	SPDIF audio, Analog 3.5mm headphone jack
Speakers	20 watt built in speakers
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

### TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

\*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.

# SB4660HDi



## 46" Signature Series True Outdoor All-Weather LCD Television for permanent outdoor installation

- Bright 46" Full HD 1080p LCD screen for improved outdoor viewing.
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- ASA outdoor rated high-impact resin exterior
- Weatherproof built in 20W speakers
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-Out prevents unauthorized users from changing the programming



### SCREEN

LCD Screen	46-inch diagonal TFT Active Matrix LCD
Resolution	1920 x 1080 Full-HD 1080p
Aspect Ratio	16:9
Contrast Ratio	4000:1
Frame Rate	60 Hz
Viewing Angle	176° x 176°
Response Time	8.0 milliseconds
TV formats	1080p, 1080i, 720p, 576p, 576i

### PHYSICAL SPECS

Accessories Included	Weatherproof remote control and outdoor dust cover
Exterior	Outdoor rated ASA high impact resin
Exterior colour	Silver
TV Dimensions (cm)	115.6 W x 74 H x 17 D
TV Weight	30 kg
Shipping Dimensions (cm)	132 W x 106.6 H x 33 D
Shipping Weight	36 kg
Warranty	One-year parts and labour

### CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 4
Video Composite	S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	TosLink Digital Optical x 1, Analog 3.5mm headphone jack
Speakers	20 watt built in speakers
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

### TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

\*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.

# SB5560HDi



## 55" Signature Series True Outdoor All-Weather LCD Television for permanent outdoor installation

- Bright 55" Full HD 1080p 120 Hz LCD screen for improved outdoor viewing
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- ASA outdoor rated high-impact resin exterior
- Weatherproof built in 20W speakers
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-Out prevents unauthorized users from changing the programming



### SCREEN

LCD Screen	55-inch diagonal TFT Active Matrix LCD
Resolution	1920 x 1080 Full-HD 1080p
Aspect Ratio	16:9
Contrast Ratio	5000:1
Frame Rate	120 Hz
Viewing Angle	176° x 176°
Response Time	6.5 milliseconds
TV formats	1080p, 1080i, 720p, 576p, 576i

### PHYSICAL SPECS

Accessories Included	Weatherproof remote control and outdoor dust cover
Exterior	Resin
Exterior colour	Silver
TV Dimensions (cm)	135.6 W x 86 H x 18.5 D
TV Weight	49 kg
Shipping Dimensions (cm)	152.4 W x 116.8 H x 33 D
Shipping Weight	58 kg
Warranty	One-year parts and labour

### CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 2
Video Composite	S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	SPDIF Audio, Analog 3.5mm headphone jack
Speakers	20 watt built in speakers
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

### TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

\*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.

# SB6560HDi



## 65" Signature Series True Outdoor All-Weather LED Television for permanent outdoor installation

- Bright 65" Full HD 1080p 240 Hz LED screen for improved outdoor viewing
- Exterior designed to protect internal components from rain, dust, insects, humidity, and salt air
- Multi-fan airflow system keeps the unit cool and dry in temperatures up to 50°C
- Ability to operate in cold weather (-31°C)
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- Powdercoated aluminium exterior
- Weatherproof detachable 20W speaker module
- Weatherproof remote control
- Weatherproof control buttons
- Remote Control Lock-out prevents unauthorized users from changing the programming



### SCREEN

LED Screen	65-inch diagonal TFT Active Matrix LED
Resolution	1920 x 1080 Full-HD 1080p
Aspect Ratio	16:9
Contrast Ratio	5000:1
Frame Rate	240 Hz
Viewing Angle	176° x 176°
Response Time	6.5 milliseconds
TV formats	1080p, 1080i, 720p, 576p, 576i

### PHYSICAL SPECS

Accessories Included	Weatherproof remote control and outdoor dust cover
Exterior	Powdercoated aluminium
Exterior colour	Silver
TV Dimensions (cm)	154 W x 91 H x 19 D
TV Weight	49 kg
Shipping Dimensions (cm)	173 W x 122 H x 33 D
Shipping Weight	58 kg
Warranty	One-year parts and labour

### CONNECTIONS

RF	Antenna/CATV (ATSC/QAM/NTSC) x 1
HDMI	HDMI™ Input x 4
Video Composite	S-Video x 1 and Composite Video x 1, L/R Audio Inputs x 1
Video Component	YPbPr plus Stereo Audio x 2
PC	15-pin D-sub VGA plus Stereo Audio
Control Set	RS232 Serial, Discrete IR Control, Concealed IR Window
Audio Out	TosLink Digital Optical x 1, Analog 3.5mm headphone jack
Speakers	20 watt detachable speaker module
Input Power	100-240 VAC, 50-60 Hz 4.0 A Max

### TEMPERATURE TOLERANCES

Operating Temp	-31° to 50°C
Non-op. Temp	-31° to 60°C*

\*Off mode with power applied. The non-operating temperature feature requires power to be applied. Specifications are subject to change without notice.